

Specifications

YSP-CU2500

Amplifier section

- Rated Output Power
Tweeter (1 kHz, 1% THD, 4 Ω) 27.2 W
- Maximum Effective Output Power
Tweeter (1 kHz, 10% THD, 4 Ω) 32 W

Speaker section

- Speaker Type...Acoustic Suspension/Magnetic Shielding type
- Driver
Tweeter 2.8 cm (1-1/8 in) Cone × 16
- Impedance 4 Ω

Input jack

- Audio Input
Optical 2 (TV, OPTICAL)
Coaxial..... 1 (AUX2)
Analog 1 pair (AUX1)
- HDMI Input 3 (HDMI IN 1 to 3)

Output jack

- HDMI Output (ARC)..... 1
- Headphones 1
- Subwoofer Output..... 1

Other jack

- INTELLIBEAM MIC 1
- SYSTEM CONNECTOR 1

Bluetooth

- *Bluetooth* version..... Ver. 2.1 +EDR
- Supported protocols A2DP, SPP
- Supported codecs SBC, aptX
- Wireless output..... *Bluetooth* Class 2
- Maximum communication distance 10 m (33 ft)
(without interference)
- Protection of supported content.....SCMS-T scheme

General

- Power Supply
[U.S.A. and Canada models] AC 120 V, 60 Hz
[Taiwan model] AC 110–120 V, 50/60 Hz
[China model] AC 220 V, 50 Hz
[Other models] AC 220–240 V, 50/60 Hz
- Power Consumption 24 W
- Standby Power Consumption
HDMI CONTROL ON and
Bluetooth Standby ON Less than 1.2 W
HDMI CONTROL OFF and
Bluetooth Standby ON Less than 0.5 W
HDMI CONTROL OFF and
Bluetooth Standby OFF Less than 0.4 W
- Dimensions (W × H × D)
When the legs are adjusted to a minimum height
..... 944 × 73 × 144 mm (37-1/8 × 2-7/8 × 5-5/8 in)
- Weight 4.0 kg (8.8 lbs)

NS-WSW120

- Driver..... 10 cm (4 in) cone woofer × 2
non-magnetic shielding type
- INPUT jack 1
- SYSTEM CONNECTOR jack 1
- Output power 75 W (100 Hz, 5 Ω, 10% T.H.D)
- Dynamic power 130 W
- Frequency response 40 Hz–500 Hz
- Wireless
Frequency 2.4 GHz
Transmission Range..... 10 m (33 ft)
(without interference)
- Power supply
[U.S.A. and Canada models] AC 120 V, 60 Hz
[Taiwan model] AC 110–120 V, 60 Hz
[Australia model] AC 240 V, 50 Hz
[U.K. and Europe models] AC 230 V, 50 Hz
[China model] AC 220 V, 50 Hz
[Korea model] AC 220 V, 60 Hz
[Asia model] AC 220–240 V, 50/60 Hz
- Power consumption 75 W
- Standby Power Consumption
Wireless..... 1.6 W
Wired 1.5 W
- Dimensions (W × H × D)
Upright positioning
..... 147 × 444 × 353 mm (5-3/4 × 17-1/2 × 13-7/8 in)
Positioned on side
..... 434 × 129 × 353 mm (17-1/8 × 5-1/8 × 13-7/8 in)
- Weight 7.9 kg (17.4 lbs)

YSP-CU2500 + NS-WSW120

- Frequency Response..... 40 Hz to 22 kHz (-10 dB)
- Crossover frequency..... 500 Hz

Specifications are subject to change without notice.